



Kimseed International Pty Ltd

ACN 108 508 336
4/5 Collingwood St
Tel: 61-8-94464377
Western Australia

ABN 37 108 508 336
Osborne Park 6017
Fax: 61-8-94463444
www.kimseed.com.au

Email: kimseed@kimseed.com.au


Kimseed Linkage Tree Planter/Seeder

The Kimseed Linkage Tree Planter/Seeder is ideal for a range of plants from bare rooted seedlings to large pots. The planter is designed for 3PL, Cat I or II, with a seedling carrying capacity of up to 500 seedlings. The soil opener is adjustable for pot sizes from 40mm to 150 mm diameters and performs well in heavy soil types.

- Specially designed opener - ideal for mound planting
 - is an adjustable heavy-duty unit
 - moves independently of the press-wheel chariot
 - allows greater operator comfort and increased compaction at the press-wheel.
- Direct seeding attachment
 - available with a seed box capacity of 10L.
 - handles all seed types from eucalyptus to saltbush
 - rate adjustment is via a sliding cog which is belt driven

Features:


- Coulter wheel
 - 550mm diameter for increased operator safety allows implement to roll up over immovable buried objects.
 - Provides excellent trash control
- Adjustable soil opener



Linkage Planter with Direct Seeder



Planter behind Kimseed Modular Ripper Furrower – tractor drawn



Planter behind Kimseed Modular Ripper Moulder – tractor drawn



Planter behind Kimseed Modular Ripper Moulder

Sustainable Land Management and Practical Applications Since 1970

Australian Native
Seed Specialists

Seed & Revegetation
Equipment

Engineering Design
& Fabrication

Forestry
Management

International Environmental
Consultants



"OPTIONAL ATTACHMENTS"

Trailing Frame for 4WD Vehicle towed with 12 Volt- DC lift

- No Tractor Required.
- 12 V- DC over Hydraulic Lift controlled by cable to driver or operator.
- Adjustable soil opener up to 150 mm
- Coulter wheel - Safely rolls over objects
- Slices into heavy soils



Direct Seeding Attachment Features



- Seed box volume: 10L
- Handles all seed types from Eucalyptus to Saltbush
- Window to check seed flow
- Sliding cog seed metering rate adjustment
- Drives on any ground wheel

Direct Seeder Attachment

Sustainable Land Management and Practical Applications Since 1970

Australian Native
Seed Specialists

Seed & Revegetation
Equipment


Engineering Design
& Fabrication

Forestry
Management

International Environmental
Consultants

General Specification

Coulter and adjustable opener and seeding tine




Soil Working Details:

- Soil opener adjustable for pot sizes: 40mm - 150mm, diameter
- Maximum penetration : 200mm, (8")
- Coulter wheel diameter 550mm
- Press Wheel Tyres: 175 x 14x 4 Ply
 - Tyre Pressure: 68 Kpa

Press Wheels Adjustments

- Press Wheels can be adjusted to suit the soil opener adjustments
- Loosen up nuts and move wheel axles to the desired position.
- Re-tighten nuts



Planter Specifications

- Implement Type: 3PL Cat I and II
- Power of Tractor: min 26kw (35hp)
- Distance metering chain: 1 – 3m
- Tray carrying capacity per tray
 - 500 x dia 50 mm pots
 - 120 x dia 100 mm pots
 - 56 x dia 150 mm pots

Shipping Details

- Net Wt. : 250 kg
- Gross Wt. 350 kg
- Inside Dimension: 1.3 L X 0.84 H X 1.23 W (m)
- Outside Dimension: 1.4 L X 1.04 H X 1.33 W (m)

Sustainable Land Management and Practical Applications Since 1970